



TRUCK MOUNTED PERCUSSION RC DRILL RIG 8000 - BASIC SPECIFICATIONS



TRUCK MOUNTED PERCUSSION - RC DRILL RIG 8000 - BASIC SPECIFICATIONS



Mast

Tubular Steel Construction working with two cylinders (no chains or cables).

Overall length – 11 meters

Overall depth – 400 mm

Overall width – 600 mm

Stroke – 7 meters

Pull-back force @ 180 bar = 221 kilo newton

Pull-down force @ 180 bar = 130 kilo newton

Pull-down feed speed = 0.46 meter per second

Pull-up feed speed = 0.27 meter per second

Pull-down feed speed rapid = 0.598 meter per second

Pull-up feed speed rapid = 0.353 meter per second

Breakout System

Manual keeper spanner

Conventional hydraulic assisted breaker spanner

Water Pump

Hydraulically driven 3 stage piston pump

Flow rate – 40 liters per minute

Maximum pressure – 40 bar

Carousel

Conventional 8 rod carousel

Carousel capacity – 8 x 6 meter rods = 48 meters

Rotation Head

Reduction gearbox type (grease filled)

Reduction 3.25:1

Through spindle hole 80 mm

RPM 0 – 80 rpm

4 x 407cc Hydraulic Motors

Torque – 18000 newton meter

Spindle thread – 102 ARD

This head can be used for both Percussion and Reverse Circulation drilling

Outriggers

4 x steel boxed hydraulic outriggers

Bore size – 100 mm

Cylinder Stroke – 1 meter

Outriggers all fitted with double pilot-operated check valves in case of hose failure.

Drilling Capacities

(Hydraulic capability of drill rig)

1000 meters @ 6.5 inches

Hole sizes – 112 mm to 400 mm





Hydraulic System

Hydraulic pump – 3 stage bushing gear pump type
Capacity – 80 / 60 / 50 cc per rev
Operating Pressure – 180 bar
Cylinders – In-house manufactured hydraulic cylinders
with standard type generic seals
Valve Banks – Casappa –
Half Inch and one inch valve sections
Hydraulic Motors – Parker
System Capacity – 450 liters



Hydraulic Head Tilt

To assist in easy and safe loading of drill rods
from the rear side of the machine.

Power Pack

Kirloskar HA 694 TC
Rated Horsepower – 110
Torque – 369 newton meter
Fuel burn at full load – 15.1 litre per hour
Maximum RPM - 2300

Oil Feeder

Ventury type oil feeding system
Capacity – 10 liters

Winch

Worm Drive Gearbox Type Hydraulically Driven Winch
Maximum weight capacity of 1 ton at a feed rate of
1 meter per second

Dump Mast Facility

Two meter travel to assist in inserting of casing adding stability to
the mast whilst drilling in both vertical and angular drilling

NOTES:

There are various options available on these rigs regarding on board or separate compressor configuration as well as different compressor sizes. These specs are based at the capacity of the standard pump and 180 bar pressure. This could easily be changed simply by changing the hydraulic pump pressure and flow rate

